



**IMPROVED
FORMULA!**

IMPROVED FORMULA HI-TEMP SPRAY ADHESIVE



New improved pressure sensitive formula gives an aggressive adhesion on many surfaces including foam, metal, fabrics, wood and DEI's heat and sound barrier materials.

All new redesigned larger can with improved nozzle and spray pattern allows for efficient and accurate use of the adhesive, while providing excellent coverage.

Advantages

- California Compliant Low VOC SCAQMD Rule 1168
- Very Aggressive, High Tack Adhesive
- Single Sided Application
- High Build Web Spray
- High Strength, long-term bond
- No ODS (ozone depleting substances)
- HAPs FREE (Hazardous Air Pollutants)
- 2-4 Minute dry time
- Heat Resistance to 200°F
- 12 cans to a case

HI-TEMP ADHESIVE SPRAY

Part #	Description
10492	13.3 OZ SPRAY CAN

**IMPROVED
CAN
DESIGN**



**STRONGER
ADHESIVE**

**LARGER
CAN
SIZE**

FOR MORE INFORMATION AND OUR COMPLETE PRODUCT LINE GO TO

DesignEngineering.com    

604 Moore Rd. Avon Lake, Ohio 44012

800-264-9472 • 440-930-7940 • (F) 440-930-7967

sales@designengineering.com